

JSC Safety and Health Handbook	JPR No.	1700.1K
	Effective Date:	11/25/2013
	Expiration Date:	11/25/2018
	Page Number	Page 9.1-1 of 12

Chapter 9.1 Hazardous Materials Safety and Health

This could be you . . .

A diesel spill occurred in a parking lot when a personal diesel container in the back of a pickup truck tipped over and leaked.

Two workers cleaning an oxidizer storage tank were killed when the tank exploded due to a reaction between the cleaning agent and residual oxidizer.

9.1.1 Applicability of this chapter

You are required to follow this chapter if you purchase or handle hazardous materials or control areas where hazardous materials are used or stored at JSC or JSC field sites.

9.1.2 What this chapter covers

This chapter covers the purchase, use, handling, transporting, and restrictions of hazardous materials. This chapter addresses current Hazard Communication requirements under the OSHA HazCom 2012 standard. Recent changes to 29 CFR 1910.1200, to meet the United Nations (UN) Globally Harmonized System of Classification and Labeling of Chemicals (GHS), give manufacturers until May 30, 2015 to comply with the new requirements.

9.1.3 What are hazardous materials?

9.1.3.1 A hazardous material is anything that can be a danger by contact, inhalation, consumption, or impacting the environment. These materials may include:

- a. Chemicals as listed in various regulations (see <http://sd.jsc.nasa.gov/omoh/scripts/OccupationalHealth/HazardousMaterials.aspx>)
- b. Radioactive materials
- c. Explosives or any pyrotechnics
- d. Pesticides

9.1.4 What to do when you need to use a hazardous material that is a risk to health, safety, or the environment

9.1.4.1 If you use or store, or plan to use or store, hazardous materials, you shall:

- a. Complete a new or update an existing hazard analysis (see paragraph 9.1.6 below) for new materials or new uses of existing materials. Obtain a Material Safety Data Sheet (MSDS)/Safety Data Sheet (SDS) during your planning to use a new material. Notify the Occupational Health Branch before you use any hazardous materials for the first time or before using a hazardous material in a new or different way.
- b. Request MSDSs/SDSs from the manufacturer or supplier whenever you order a hazardous material. If they did not provide the MSDS/SDS for your hazardous material, contact them immediately for a copy. You may not use the material until you have an MSDS/SDS annotated

JSC Safety and Health Handbook	JPR No.	1700.1K
	Effective Date:	11/25/2013
	Expiration Date:	11/25/2018
	Page Number	Page 9.1-2 of 12

with a “JSC MSDS/SDS Number” and have addressed the identified hazards. (See paragraphs 9.1.8 and 9.1.9 below.)

- (1) Keep MSDSs/SDSs up to date by having procedures for filing revised or newly acquired MSDSs/SDSs from the JSC MSDS/SDS repository or supplier.
 - (2) Provide new or revised MSDSs/SDSs to the Occupational Health Branch.
 - (3) Keep a hard copy of your MSDSs/SDSs readily available for employees in the work area.
- c. Review proposed purchases against the list of restricted and prohibited materials before starting a purchase request or supply requisition.
 - d. Get a waiver before using any prohibited material or materials with a restricted use as described in paragraph 9.1.15 below.
 - e. Contact the JSC Radiation Safety Officer before purchasing radioactive materials (see Chapter 7.3 of this Handbook).
 - f. Review hazardous waste disposal requirements of residual, used, or contaminated material as well as empty containers to determine the cost impacts, environmental impacts, or regulatory restrictions. Regulations may require substitution of certain materials. For example, stratospheric ozone-depleting chemicals should be phased out under the Clean Air Act of 1990. See Chapter 5.8, “Hazardous Operations: Safe Practices and Certification,” of this Handbook for more information on permits. See Chapter 4.1, “Safety and Health Training,” for more information on safety and health training.
 - g. Try to find a less hazardous material that will do the job within your quality standards.
 - h. Purchase the smallest quantity necessary to do the job.
 - i. Develop and maintain a list of hazardous materials in the JSC Hazardous Material Inventory Database. See Chapter 9.2, “Hazard Communication,” of this Handbook.
 - j. Make sure that you and your employees are properly trained in the use and hazards of these materials before using them. See Chapter 9.2, “Hazard Communication,” of this Handbook.
 - k. Use proper work practices and handling procedures.
 - l. Use proper waste-handling practices, such as labeling, segregating, and avoiding the mixing of different hazardous waste streams.
 - m. Make sure that all hazardous materials are used properly and that necessary precautions are taken so that no harm is done to humans or the environment.
 - n. Make sure that your subcontractors who use hazardous materials on site follow the requirements of this chapter if you are a prime contractor.
 - o. Make sure your visiting scientists who use hazardous materials follow the requirements of this chapter.

JSC Safety and Health Handbook	JPR No.	1700.1K
	Effective Date:	11/25/2013
	Expiration Date:	11/25/2018
	Page Number	Page 9.1-3 of 12

9.1.5 Recycling

Recycling hazardous materials is another method of reducing cost and minimizing wastes while conserving natural resources. Before recycling hazardous materials, contact the Environmental Office to determine environmental requirements.

9.1.6 Planning to handle hazardous materials

9.1.6.1 If you are planning to handle hazardous materials, you shall complete a hazard analysis for each process that you control, or that is in your area, that uses toxic, reactive, flammable, radioactive, or corrosive chemicals. The hazard analysis will help to establish precautionary measures and help to determine the need for an emergency action plan (EAP). Obtain and use the most current MSDS/SDS when performing the hazard analyses. The hazard analysis shall:

- a. Contain a listing of chemicals used in the process.
- b. Be updated whenever quantities increase or processes change.
- c. Address the failure mode of the spontaneous release, such as a container failure without operations in progress.

NOTE: See Chapter 2.3, "Hazard Analysis," and JSC 17773, "Preparing Hazard Analysis for JSC Ground Operations," for instructions on completing the hazard analysis. Follow Chapter 3.3, "Process Safety Management," and 29 CFR 1910.119 for process safety management of highly hazardous chemicals.

9.1.7 What to do with a completed hazard analysis

9.1.7.1 If your analysis shows hazards with an RAC of 1, 2, or 3 as described in Chapter 3.5, "Hazard Correction Tracking," of this Handbook, you shall:

- a. Prioritize control measures using this order: engineering controls, administrative controls, work practices and personal protective equipment (PPE).
- b. Send a list of the hazards to the Occupational Health Branch (SD3229) for review.
- c. Develop or modify your EAP to cover the actions that need to be taken to ensure employee safety during fires, hazardous material releases, or other emergencies that might occur in your area. Your EAP shall follow the requirements in Chapter 3.8, "Emergency Preparedness," of this Handbook.

9.1.8 Responsibility for MSDSs/SDSs at JSC

9.1.8.1 Under recent changes to OSHA 29 CFR 1910.1200 for compliance with GHS requirements, the term Material Safety Data Sheet (MSDS) will be changing to Safety Data Sheet (SDS). Manufacturers have until May 30, 2015 to produce SDSs compliant with 29 CFR 1910.1200 and GHS.

The following applies to MSDSs/SDSs:

- a. Line organizations who acquire hazardous materials shall obtain a current MSDS/SDS using the process in paragraph 9.1.9 below.

JSC Safety and Health Handbook	JPR No.	1700.1K
	Effective Date:	11/25/2013
	Expiration Date:	11/25/2018
	Page Number	Page 9.1-4 of 12

- b. The Occupational Health Branch keeps the central repository of MSDSs/SDSs for JSC and assists in obtaining, collecting, maintaining, and distributing MSDSs/SDSs. An on-line database of these MSDSs/SDSs is available on the Health Home page. You may contact the Occupational Health Branch MSDS/SDS Coordinator at x37512 for any questions that you may have about MSDSs/SDSs.
- c. MSDSs/SDSs for materials no longer in your inventory should be removed from your area MSDS/SDS book.
- d. By May 30, 2015 manufacturers must replace their MSDSs with current SDSs. Line organizations shall replace their MSDSs with current SDSs where available.

9.1.9 Submitting an MSDS/SDS

9.1.9.1 To submit an MSDS/SDS for inclusion into the NASA/JSC MSDS/SDS Database:

- a. First check the NASA/JSC MSDS/SDS. Search for any MSDSs/SDSs that are not in your files. If the MSDS/SDS is in the database and scanned into the system, you can print the MSDS/SDS directly off the screen.
- b. If the MSDS/SDS is in the database but is not scanned into the system, submit a completed JSC Form 277, "Request for Material Safety Data Sheets Processing" (Safety Data Sheet) (Appendix D), to the Occupational Health Branch MSDS/SDS Coordinator (SD3229). The MSDS/SDS Coordinator will contact you when the item has been scanned into the system.
- c. If the MSDS/SDS is not in the database, request a copy of the MSDS/SDS from the manufacturer or supplier of the product.
- d. If the MSDS/SDS in your work area is more than 3 years old, it may be outdated. Contact the manufacturer or supplier to determine whether a more current MSDS/SDS is available. All current MSDSs should be replaced by SDSs by May 2015.
- e. Submit all new and updated MSDSs/SDSs, along with a completed JSC Form 277, to the Occupational Health Branch MSDS/SDS Coordinator (SD3229). This individual will assign a JSC MSDS/SDS Number and will contact you when the item has been scanned into the system.

9.1.10 Purchase requests for hazardous materials

9.1.10.1 Both contractors and civil servants must follow the requirements for purchasing hazardous materials in this chapter. You shall:

- a. State, on the purchase request, "MSDS/SDS REQUIRED. RECEIVING OFFICE: UPON RECEIPT OF MSDS/SDS, FORWARD ONE COPY EACH TO CENTRAL MSDS/SDS REPOSITORY AND TO USER."
- b. Notify the Occupational Health Branch and the Environmental Office before you:
 - (1) Use any hazardous materials initially.
 - (2) Change the usage of any hazardous material.

JSC Safety and Health Handbook	JPR No.	1700.1K
	Effective Date:	11/25/2013
	Expiration Date:	11/25/2018
	Page Number	Page 9.1-5 of 12

9.1.11 The role of procurement in purchasing hazardous materials

- a. The Procurement Support Group shall:
 - (1) Support procurement in identifying contract requirements for safety concerns under JPR 1281.6, "Procurement."
 - (2) Coordinate all procurements involving hazardous materials with the Occupational Health Branch to identify requirements that the supplier must follow and document. The Occupational Health Branch requires an MSDS/SDS to accompany the shipment.
- b. Procurements of any potentially hazardous material shall follow subpart 23.3 of the Federal Acquisition Regulations (FAR) and NASA FAR Supplement, NFS 1823.3, "Hazardous Material Identification and Material Safety Data."
- c. All procurement offices shall ensure that specific safety or health requirements are included in purchase orders and contracts. Specifically, safety or health requirements will indicate whether an MSDS/SDS is necessary.

9.1.12 Responsibilities of the receiving office

9.1.12.1 All receiving offices shall:

- a. Ensure that an MSDS/SDS accompanies all hazardous materials when specified on the purchase order.
- b. Confirm that each shipping container has a label that identifies the contents given on the MSDS/SDS, the manufacturer or distributor of the material, and the specific physical or health hazards cited in the MSDS/SDS.
- c. Send all MSDSs/SDSs that accompany any shipments of materials to the Central MSDS/SDS Repository (SD3229). You shall keep copies of the original MSDS/SDS in the receiving office repository to be distributed later with the material.
- d. Ensure a copy of the MSDS/SDS accompanies all hazardous materials in storage and distribution either on site or off site. MSDSs/SDSs shall be made available to receiving office employees on request.
- e. Ensure receiving office employees are trained in the measures to take in the event of a spill or leak of hazardous materials.
- f. Immediately impound the material and contact the responsible forwarding office for correction if the MSDS/SDS is missing from the shipping documents. If an MSDS/SDS is already on file, the receiving office may add this MSDS/SDS to the shipping papers if the name and supplier of the material on the shipping container and the MSDS/SDS are identical. The exception to this is generic materials such as hydrochloric acid or caustic soda.
- g. Reject and return any shipment or transfer of hazardous materials if the supplier or forwarding office fails to provide an MSDS/SDS.

JSC Safety and Health Handbook	JPR No.	1700.1K
	Effective Date:	11/25/2013
	Expiration Date:	11/25/2018
	Page Number	Page 9.1-6 of 12

9.1.13 Safely handling and storing hazardous materials

9.1.13.1 If you have hazardous materials in your work areas, you shall also:

- a. Review the hazardous materials in your work area to:
 - (1) Reduce the quantity of the material.
 - (2) Reduce the chance of a fire, a spill, or an accidental release.
 - (3) Reduce hazardous waste.
- b. Take steps to eliminate or reduce the risks of hazardous materials. This includes substituting a less hazardous material, if possible, or writing work requests, as necessary, to install required engineering controls. Excessing or disposing of any hazardous materials that have not been used within the past three years will also reduce the risks.
- c. Never retain peroxide-forming chemicals for more than one year after purchase.
- d. Keep the proper fire extinguishers in the area. Contact the Safety and Test Operations Division for more information.
- e. Store hazardous materials in a manner consistent with manufacturer’s recommendations and the Chemical Segregation and Storage Guide found on the Health home page.
- f. Post appropriate warning signs within your work areas, and make sure that tanks and piping are labeled per ASME A13.1, “Scheme for the Identification of Piping Systems.”
- g. Label all containers of hazardous materials within your work area as described in 29 CFR 1910.1200, “Hazard Communication Standard” (see Chapter 9.2 of this Handbook).
- h. Use proper waste-handling practices, including waste segregation and disposal, for all processes that use hazardous materials, per the Waste Segregation and Storage Guide found in JPR 8550.1, “Environmental Compliance Procedural Requirements.”
- i. Make sure you have appropriate fire protection systems and fire extinguishers for the hazardous materials.
- j. Make an assessment for the need for escape respirators in areas where hazardous materials are stored.
- k. Make sure chemical alarms and warning lights are operational as described in Chapter 6.12, “Local Hazard Chemical Alarms,” of this Handbook.
- l. Assess the condition of hazardous materials in storage at least quarterly and remove those you determine to be unsuitable.
- m. Never keep food and drink in any refrigerators or freezers where hazardous materials are stored.
- n. Follow the requirements in paragraph 3.7 of NPR 8715.3.

9.1.14 Restricted and prohibited materials at JSC

9.1.14.1 JSC has decided that some products are too hazardous to handle and are prohibited for purchase, storage, or use. Other products are toxic or highly regulated and may only be used

JSC Safety and Health Handbook	JPR No.	1700.1K
	Effective Date:	11/25/2013
	Expiration Date:	11/25/2018
	Page Number	Page 9.1-7 of 12

in limited applications, or restrictions may apply. See the following URL for the list of restricted and prohibited chemicals:

<http://sd.jsc.nasa.gov/omoh/docs/Restricted%20and%20Prohibited%20Materials.doc>

The following requirements apply:

- a. JM/Project Management Office shall maintain JSC SPECSINTACT to conform to the policy on restricted materials that may be used in construction, modification, or repair of facilities, specifically asbestos-containing materials (ACMs), PCBs, chlorofluorocarbons (CFCs) and hydro-chlorofluorocarbons, and mercury.
- b. If you are responsible for maintaining facilities or equipment, you shall specify “non-asbestos” products, undetectable concentrations of PCBs, “non-CFC”-containing equipment, or non-mercury equipment.

NOTE: JSC is continually evaluating the restricted and prohibited materials list. Before purchasing or using a material, check the most current list at

<http://sd.jsc.nasa.gov/omoh/scripts/OccupationalHealth/MSDS.aspx>

9.1.15 Waivers to use a restricted or prohibited material

9.1.15.1 You may request a temporary waiver if the use of a specific restricted or prohibited material is required to achieve JSC’s mission. You shall submit your waiver request in writing to the JE/Environmental Office. The Environmental Office will coordinate review of the waiver request, as appropriate, with the Occupational Health Branch or the Safety and Test Operations Division. A waiver request form is available at <http://sd.jsc.nasa.gov/omoh/scripts/OccupationalHealth/MSDS.aspx> .

The following requirements apply:

- a. Your temporary waiver request shall include the following information:
 - (1) Name and phone number of requestor.
 - (2) Organization name and mail code if NASA (or onsite contractor).
 - (3) Contract name and number if contractor.
 - (4) Name and Chemical Abstract Service number of chemical.
 - (5) Location(s) of proposed use (building and room number).
 - (6) Description of proposed process using chemical.
 - (7) Estimated quantity of the chemical that you expect to store and use per year for each location.
 - (8) Justification for use of the restricted or prohibited chemical. If no alternative is available for the chemical, you shall provide documentation of your efforts to locate an alternative.
 - (9) If a specification, standard, or contract line item requires the use of this specific chemical, you shall provide a reference to that requirement (contract name and number and contract line item or procedure name and number) and a copy of the requirement.

JSC Safety and Health Handbook	JPR No.	1700.1K
	Effective Date:	11/25/2013
	Expiration Date:	11/25/2018
	Page Number	Page 9.1-8 of 12

(10) A copy of the hazard analysis and trade studies (if applicable) for the proposed activity or process that will use the chemical. Include any assessments of alternative materials.

- b. The Environmental Office and the Occupational Health Branch shall approve and sign your temporary waiver before you may use the restricted or prohibited chemical. If a new chemical is placed on the restricted and prohibited chemical list, you have 6 months in which to re-evaluate the process and find an alternative or request a temporary waiver.
- c. Temporary waivers stay in effect for a designated time period of between 1 and 5 years, depending on the safety, health, and environmental characteristics of the chemical. You shall apply for a new waiver and have it approved before the expiration date of an existing waiver to continue using the chemical.

9.1.16 Other material restrictions

9.1.16.1 The following materials, in concentrations specified in the standards listed below, are subject to certain restrictions under 40 CFR 61, “National Emission Standards for Hazardous Air Pollutants” (NESHAP), or under OSHA substance-specific standards. These materials shall follow:

- a. NESHAP restrictions found in this table.

<i>For . . .</i>	<i>Follow this subpart of 40 CFR 61 . . .</i>
Asbestos	M
Beryllium	C
Mercury	E
Vinyl chloride	F
Radionuclides	I
Benzene	J, Y, BB, and FF

- b. OSHA restrictions in 29 CFR 1910, “Occupational Safety and Health Standards, General Industry:”

<i>For . . .</i>	<i>Follow 29 CFR 1910 . . .</i>
Asbestos	1001
4-nitrobiphenyl	1003
Alpha-naphthylamine	1003
Methyl chloromethyl ether	1003
3,3-dichlorobenzidine and salts	1003
Bis-chloromethyl ether	1003
Beta-naphthylamine	1003
Benzedrine	1003
4-aminodiphenyl	1003
Ethyleneimine	1003
Beta-propiolactone	1003

JSC Safety and Health Handbook	JPR No.	1700.1K
	Effective Date:	11/25/2013
	Expiration Date:	11/25/2018
	Page Number	Page 9.1-9 of 12

<i>For . . .</i>	<i>Follow 29 CFR 1910 . . .</i>
2-acetylaminofluorene	1003
4-dimethylaminoazobenzene	1003
N-nitrosodimethylamine	1003
Vinyl chloride	1017
Inorganic arsenic	1018
Lead	1025
Cadmium	1027
Benzene	1028
1,2-dibromo-3-chloropropane	1044
Acrylonitrile	1045
Ethylene oxide	1047
Formaldehyde	1048
Methylenedianiline	1050
1,3 Butadiene	1051
Methylene Chloride	1052

- c. OSHA restrictions in 29 CFR 1926, "Occupational Safety and Health Standards, Construction Industry:"

<i>For . . .</i>	<i>Follow 29 CFR 1926 . . .</i>
Asbestos	1101
Cadmium	1127
Lead	62
Methylenedianiline	60

9.1.17 Requesting transportation of hazardous materials

9.1.17.1 You shall use the following procedure for requesting transportation of hazardous materials:

- a. Contact Transportation Work Control at x42409 as much in advance as possible. Transportation resources are limited, and different kinds of hazardous materials cannot be transported together. Schedule transportation of compressed gas cylinders in advance since they are transported on a cylinder truck.
- b. Identify the hazardous material, the amount, the weight, the type of container, and locations for transport. Have an MSDS/SDS for the material available at the time of pickup.
- c. The dispatcher will prepare a work order and the pickup will be scheduled. Depending on workload and the availability of equipment, work stoppage and rush shipments may be accommodated.

JSC Safety and Health Handbook	JPR No.	1700.1K
	Effective Date:	11/25/2013
	Expiration Date:	11/25/2018
	Page Number	Page 9.1-10 of 12

d. Handle gas cylinders as described in JPR 1710.13, "Design, Inspection, and Certification of Pressure Vessels and Pressurized Systems."

9.1.18 Transporting hazardous materials

9.1.18.1 You shall follow these requirements:

- a. Follow paragraph 3.7.5 of NPR 8715.3, "NASA General Safety Program Requirements."
- b. Never transport hazardous materials on site or on public roads in your car, truck, any other privately owned vehicle, or NASA administrative aircraft. You may be denied access to the site if you try to transport hazardous materials outside of the acceptable conditions specified below:
 - (1) Household concentrations on site in quantities of less than 5 gallons.
 - (2) Small quantities of chemicals for analytical purposes in a government or an official company vehicle. You shall not travel on public roads unless approved as described in (4) below.
 - (3) Small quantities of hazardous materials that are unopened and packaged in the original DOT-approved shipping containers and only in government or official company vehicles. You shall not travel public roads unless approved as described in (4) below.
 - (4) Small quantities of approved hazardous materials in a government or an official company vehicle on public roads and meeting the requirements in "JSC Hazardous Material Hand-Carry Provisions" at URL:
<http://sd.jsc.nasa.gov/omoh/docs/HAZMAT%20Hand%20Carry%20Process.docx>.
 - (5) Craftspeople may transport hazardous materials that are specific to their craft and are essential to their work in a government or official company vehicle designed for that task; they shall not travel on public roads. Examples include welders who transport compressed gas cylinders, custodial workers who transport cleaning fluids, and pesticide applicators who transport pesticides to application sites.
- c. Route any hazardous materials leaving JSC, Ellington Field, or Sonny Carter Training Facility that will travel on public roads through the Transportation Branch for appropriate handling per 49 CFR, Subchapter C, "Hazardous Materials Regulations." This includes any materials transported between JSC ("inside the fence"), Sonny Carter Training Facility, and Ellington Field.
- d. The Center Operations support services contractor is the only organization authorized to transport hazardous waste.
- e. The JSC Radiation Safety Officer or his or her designee is the only person authorized to transport radioactive materials.

9.1.19 Reporting an accident while transporting hazardous materials

9.1.19.1 In general, contracted commercial carriers are responsible by law for reporting all accidents involving transportation of hazardous materials. If you are transporting hazardous

JSC Safety and Health Handbook	JPR No.	1700.1K
	Effective Date:	11/25/2013
	Expiration Date:	11/25/2018
	Page Number	Page 9.1-11 of 12

materials using JSC equipment and have an accident in the public domain, you shall report the accident by:

- a. Calling the DOT Accident Hotline (800-424-8802) if it involves any of the following:
 - (1) A fatality
 - (2) A person requiring hospitalization as a result of injuries received
 - (3) Estimated property damage exceeding \$50,000
 - (4) Possible existence of radioactive contamination
 - (5) A continuous danger existing at the site, such as a spill or leakage of hazardous material
- b. Notifying the JSC Safety and Test Operations Division Emergency Hotline at x34900 and the JSC Transportation Branch at x32301. They will help you meet other requirements.

NOTE: At WSTF, you shall notify the NASA Safety Officer (Safety and Mission Assurance Office) and the Chief, Engineering Office. The WSTF Safety Officer will notify the JSC Director, Safety and Mission Assurance, for you.
- c. Follow Chapter 2.6, “Mishap and Incident Investigation,” of this Handbook for further guidance on mishap reporting and investigation.

9.1.19.2 The Director, Safety and Mission Assurance, shall notify the NASA Headquarters Safety and Risk Management Division of the accident and will make sure that the DOT has been notified. This includes sending a written follow-up report to the Associate Director for Hazardous Materials Regulations, DOT, Washington, D.C. 20590, within 15 days as stated in 49 CFR 171.16, “Detailed Hazardous Materials Incident Reports.” It also includes sending copies to the NASA Safety Division, Office of the Chief Engineer, NASA Headquarters.

9.1.20 Reporting emergencies

You shall report all emergencies at JSC and Ellington Field by calling your emergency number - x33333 or (281) 483-3333 for JSC, Sonny Carter Training Facility, and Ellington Field; 911 off site; and x5911 at WSTF.

9.1.21 Emergency response

Spills or leaks of hazardous materials often will require containment and countermeasures under EPA and OSHA regulations. Usually when a hazardous material spills or leaks into the environment or becomes an immediate threat to the safety of personnel or facilities, an emergency exists and requires immediate response under established contingency plans. Handle all leaks and spills as described in JPR 8550.1, “JSC Environmental Compliance Procedural Requirements,” mishap reporting requirements in this Handbook (see Chapter 2.6), and JSC’s emergency response plan. The Occupational Health Branch will acquire specific information on trade name products for purposes of emergency or first-aid treatment.

9.1.22 For more information on handling hazardous materials

- a. 29 CFR 1910, “Occupational Safety and Health Standards, General Industry”
- b. 29 CFR 1926, “Occupational Safety and Health Standards, Construction Industry”

JSC Safety and Health Handbook	JPR No.	1700.1K
	Effective Date:	11/25/2013
	Expiration Date:	11/25/2018
	Page Number	Page 9.1-12 of 12

- c. Clean Air Act of 1990, 42 U.S.C. Section 7401, et seq.
- d. 49 CFR Parts 171–174, “Hazardous Materials Regulations” (DOT)
- e. *Department of Transportation Emergency Response Guidebook* (latest edition)
- f. 40 CFR 61, “National Emission Standards for Hazardous Air Pollutants” (EPA)
- g. 40 CFR Parts 240–281, “Solid and Hazardous Waste Regulations” (EPA)
- h. 40 CFR Parts 370–372, “Emergency Planning and Community Right-to-Know” (EPA)
- i. 40 CFR 355, “Emergency Planning and Notification”
- j. 40 CFR 302.4, “Designation of Hazardous Substances”
- k. NPR 1800.1, “NASA Occupational Health Program Procedures”
- l. NPR 8715.3, “NASA General Safety Program Requirements”
- m. JPR 8550.1, “Environmental Compliance Procedural Requirements”
- n. National Fire Protection Association Class IA Flammable Liquids

9.1.23 Additional responsibilities for hazardous materials

- a. As a **supervisor** you are responsible for:
 - (1) Ensuring that a quarterly hazardous material inventory is completed and providing inventory information to the Occupational Health Branch in the format specified. (See Chapter 9.2 of this Handbook.) Making additions and deletions to your hazardous material inventory as they occur will make it easier to keep current.
 - (2) Providing PPE to control the hazards of the materials being handled. The Occupational Health Branch will help you select PPE.
 - (3) Following all requirements for restricted and prohibited materials.
 - (4) Developing and maintaining a hazard analysis for your processes that use hazardous materials, as described in Chapter 2.3, “Hazard Analysis,” of this Handbook and in JSC 17773.
 - (5) Ensuring that hazardous materials in your control have adequate evacuation and response procedures for a release or spill. You shall coordinate your procedures with your facility manager to ensure a unified emergency action plan for the facility.
- b. As a **facility manager**, you are responsible for ensuring that emergency action procedures you develop for your facility consider inputs from any supervisors in your facility who control hazardous materials, which, if released, could result in evacuation of your facility.